Source: All Sources: Area of Law - By Topic: Patent Law: Patents: Non-U.S. Patents: \$ Patent Abstracts | f Japan

Terms: 57099729 (Edit Search)

JP-A 57099729; JP-A 56167580; JP-A 81167580

COPYRIGHT: (C)1982, JPO & Japio

PATENT ABSTRACTS OF JAPAN

57099729

June 21, 1982

MANUFACTURE OF SEMI-AMORPHOUS SEMICONDUCTOR

INVENTOR: YAMAZAKI SHUNPEI

APPL-NO: 56167580 (JP 81167580)

FILED: October 20, 1981

ASSIGNEE: YAMAZAKI SHUNPEI

INT-CL: H01L21/205, (Section H, Class 01, Sub-class L, Group 21, Sub-group 205); //

H01L31/04, (Section H, Class 01, Sub-class L, Group 31, Sub-group 04)

REF-CITED: 55026388

ABST:

PURPOSE: To perform transformation into a semiconductor material of semi- amorphous structure suitable for a photoelectric conversion device by a method wherein through irradiation on an amorphous semiconductor by an instantaneous light or a laser light, heating to reach a temperature that is lower than a melting temperature by a specified value is performed.

CONSTITUTION: For example by glow discharge at a low temperature (normal temperature W300 [degrees] C) using SiH[4] (He based) as reaction gas, an Si film of an amorphous (AS) structure is built on a clean substrate. The AS film is annealed by plasma at the temperature of 400W600 [degrees] C that is below a crystallizing temperature in hydrogen or He, and it is changed into a semi-amorphous (SAS) structure which has an intermediate crystal structure between an AS and a crystal and is stabilized by neutralizing an unpaired bond. During this annealing process, simultaneous radiation of an instantaneous light from an Xe lamp or a laser light is performed, under a temperature lower than a melting point by 100 [degrees] C or more during the irradiation. By this method, an SAS structure can be more stabilized.

Source: All Sources: Area of Law - By Topic: Patent Law: Patents: Non-U.S. Patents: \$ Patent Abstracts of

Japan

Terms: 57099729 (Edit Search)

View: SuperKWIC

Date/Time: Tuesday, July 25, 2000 - 2:46 PM EDT

About LEXIS-NEXIS | Terms and Conditions